



MULTILIFT

Multilift Hooklift Systems

Basic Selection Parameters

Model	Capacity (lbs.)	Body Length (ft.)	Standard Hook Height (in.)	Typical Truck GVW (lbs.)	Typical Cab to Axle for Conventional Cab (in.)	Typical Cab to Axle for Tilt Cab (in.)	Typical Maximum Chassis Height (in.)
XR4N	9,000	10–11	36.6	14,000–16,000	84	108	36
XR5S (Short)	12,000	10.5–12	36.6	17,000–23,000	84	108	36
XR5N	12,000	11–14	36.6	18,000–23,000	108	120	36
XR5L	12,000	12–15	36.6	18,000–23,000	120	TBA	36
XR5XL	11,000	14–17	36.6	18,000–23,000	138	TBA	36
XR7N	16,000	11–14	36.6	23,000–30,000	108	TBA	40
XR7L	16,000	12–15	36.6	23,000–30,000	120	TBA	40
XR7XL	15,500	14–17	36.6	23,000–30,000	138	TBA	40
XR10.36	22,000	12–15	62	30,000–37,000	120–128	TBA	40
XR10.41	22,000	14–17	62	30,000–37,000	138–144	TBA	40
XR10.51	22,000	17–20	62	30,000–37,000	169–187	TBA	40
LHT190.41	31,000	14–17	62	40,000–50,000	125 (Tandem)	TBA	44
LHT190.46	31,000	15–18	62	40,000–50,000	145 (Tandem)	TBA	44
LHT190.51	31,000	17–20	62	40,000–50,000	165 (Tandem)	TBA	44
LHT190.56	31,000	18–22	62	40,000–50,000	185 (Tandem)	TBA	44
XR21.46	50,000	15–19	62	50,000–62,000	148 (Tandem)	TBA	45
XR21.56	50,000	18–22	62	50,000–62,000	186 (Tandem)	TBA	45
XR21.61	50,000	20–24	62	50,000–62,000	204 (Tandem)	TBA	45
XR26.51	60,000	16-20	62	60,000+	168 (Tandem)	TBA	45
XR26.56	60,000	18–22	62	60,000+	186 (Tandem)	TBA	45
XR26.61	60,000	20–24	62	60,000+	204 (Tandem)	TBA	45
XR26.78	60,000	25-29	62	60,000+	TBA	TBA	45


Specifications are subject to change without notice



Toll free: 1-888-799-4422 E-mail: info@atlaspol.com

www.atlaspol.com

Multitask with Multilift



Multilift Hooklift Systems