


Multitask with Multilift



Multilift Hooklift Systems



Multilift Hooklift Systems

Basic Selection Parameters

Model	Capacity (lbs.)	Body Length (ft.)	Standard Hook Height (in.)	Typical Truck GVW (lbs.)	Typical Cab to Axle for Conventional Cab (in.)	Typical Maximum Chassis Height (in.)
XR4N	9,000	10-11	36.6	14,000 - 16,000	84	36
XR5S (Short)	12,000	10.5-12	36.6	17,000-23,000	84	36
XR5N	12,000	11-14	36.6	18,000 - 23,000	108	36
XR5L	12,000	12-15	36.6	18,000-23,000	120	36
XR5XL	11,000	14-17	36.6	18,000-23,000	138	36
XR7N	16,000	11-14	36.6	23,000-30,000	108	40
XR7L	16,000	12-15	36.6	23,000-30,000	120	40
XR7XL	15,500	14-17	36.6	23,000-30,000	138	40
XR10.36	22,000	12-15	62	30,000-37,000	120-128	40
XR10.41	22,000	14-17	62	30,000-37,000	138-144	40
XR10.51	22,000	17-20	62	30,000-37,000	169-187	40
XR14.46	35,000	15-19	62	40,000-50,000	145 (Tandem)	44
XR14.51	35,000	17-20	62	40,000-50,000	165 (Tandem)	44
XR14.53	35,000	18-21	62	40,000-50,000	170 (Tandem)	44
XR21.46	50,000	15-19	62	50,000-62,000	148 (Tandem)	45
XR21.56	50,000	18-22	62	50,000-62,000	186 (Tandem)	45
XR21.61	50,000	20-24	62	50,000-62,000	204 (Tandem)	45
XR26.51	60,000	16-20	62	60,000+	168 (Tandem)	45
XR26.56	60,000	18-22	62	60,000+	186 (Tandem)	45
XR26.61	60,000	20-24	62	60,000+	204 (Tandem)	45
XR26.78	60,000	25-29	62	60,000+	TBA	45
XR30.56	72,000	18-22	62	TBA	TBA	TBA
XR30.63	72,000	21-25	62	TBA	TBA	TBA

Specifications are subject to change without notice



Atlas Polar

IT'S ALL ABOUT QUALITY™

www.atlaspolar.com

Toll free: 1-888-799-4422 E-mail: info@atlaspolar.com